



# S4000

## KALDIR & SÜR

### SÜRME SİSTEM

#### **TEKNİK ÖZELLİKLER**

TECHNICAL PROPERTIES

<b>KASA DERİNLİĞİ / FRAME DEPTH :</b>	<b>130,135,206 mm</b>
<b>KANAT DERİNLİĞİ / SASH DEPTH :</b>	<b>58 mm</b>
<b>PROFİL ET KALINLIĞI / PROFILE WALL THICKNESS :</b>	<b>1,6 mm</b>
<b>MAX. CAM KALINLIĞI / MAX GLASS THICKNESS :</b>	<b>42 mm</b>
<b>ISI BARIYERLERİ / INSULATION BARS :</b>	<b>15 mm</b>
<b>ISI YALITIM DEĞERİ (uF) / THERMAL INSULATION VALUE (uF) :</b>	<b>4,53 W/m<sup>2</sup>K</b>

#### **KULLANIM SEÇENEKLERİ**

APPLICATION ALTERNATIVES

	<b>PENCERE WINDOW</b>	<b>KAPI DOOR</b>
<b>NORMAL SÜRME / SLIDING :</b>	●	●
<b>SABİT KASA / OUTSIDE OPENING STEP :</b>	●	●
<b>ÜÇ RAYLI KASA / INWARD OPENING FLUSH :</b>	●	●
<b>SİNEKLİK UYUMU / APPLICABLE TO INSECT SCREEN :</b>	●	●